

**NEW SOURCE CONSTRUCTION PERMIT and
FEDERALLY ENFORCEABLE STATE
OPERATING PERMIT (FESOP)
OFFICE OF AIR MANAGEMENT**

**Ranger Materials Corporation
SR 114
Disko, Indiana**

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-8 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: F169-12210-00061	
Issued by: Paul Dubenetzky, Branch Chief Office of Air Management	Issuance Date:

SECTION A	SOURCE SUMMARY	5
A.1	General Information [326 IAC 2-8-3(b)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]	
A.3	Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(l)]	
A.4	FESOP Applicability [326 IAC 2-8-2]	
A.5	Prior Permit Conditions	
SECTION B	GENERAL CONDITIONS	7
B.1	Permit No Defense [IC 13]	
B.2	Definitions [326 IAC 2-8-1]	
B.3	Permit Term [326 IAC 2-8-4(2)]	
B.4	Enforceability [326 IAC 2-8-6]	
B.5	Termination of Right to Operate [326 IAC 2-8-9][326 IAC 2-8-3 (h)]	
B.6	Severability [326 IAC 2-8-4(4)]	
B.7	Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]	
B.8	Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]	
B.9	Compliance Order Issuance [326 IAC 2-8-5(b)]	
B.10	Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]	
B.11	Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]	
B.12	Annual Compliance Certification [326 IAC 2-8-5(a)(1)]	
B.13	Preventive Maintenance Plan [326 IAC 1-6-3][326 IAC 2-8-4(9)][326 IAC 2-8-5(a)(1)]	
B.14	Emergency Provisions [326 IAC 2-8-12]	
B.15	Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]	
B.16	Permit Modification, Reopening, Revocation and Reissuance, or Termination	
B.17	Permit Renewal [326 IAC 2-8-3(h)]	
B.18	Permit Amendment or Modification [326 IAC 2-8-10][326 IAC 2-8-11.1]	
B.19	Operational Flexibility [326 IAC 2-8-15]	
B.20	Permit Revision Requirement [326 IAC 2-8-11.1]	
B.21	Inspection and Entry [326 IAC 2-8-5(a)(2)]	
B.22	Transfer of Ownership or Operation [326 IAC 2-8-10]	
B.23	Annual Fee Payment [326 IAC 2-8-4(6)] [326 IAC 2-8-16]	
B.24	Advanced Source Modification Approval [326 IAC 2-8-4(11)] [326 IAC 2-1.1-9]	
SECTION C	SOURCE OPERATION CONDITIONS	17
	Emission Limitations and Standards [326 IAC 2-8-4(1)]	
C.1	Overall Source Limit [326 IAC 2-8]	
C.2	Opacity [326 IAC 5-1]	
C.3	Open Burning [326 IAC 4-1] [IC 13-17-9]	
C.4	Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]	
C.7	Operation of Equipment [326 IAC 2-8-5(a)(4)]	
C.8	Stack Height [326 IAC 1-7]	
C.9	Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]	
	Testing Requirements [326 IAC 2-8-4(3)]	
C.10	Performance Testing [326 IAC 3-6]	
	Compliance Requirements [326 IAC 2-1.1-11]	
C.11	Compliance Requirements [326 IAC 2-1.1-11]	
	Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]	

- C.12 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]
- C.13 Monitoring Methods [326 IAC 3]
- C.14 Pressure Gauge Specifications

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- C.15 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]
- C.16 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4]
- C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

- C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]
- C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

- C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

SECTION D.1 FACILITY OPERATION CONDITIONS

Batch Mix Asphalt Plant	25
--------------------------------	-----------

Construction Conditions

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.1.4 Particulate Matter (PM) [326 IAC 6-3-2] [326 IAC 12] [40 CFR 60.90, Subpart I]
- D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]
- D.1.6 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4]
- D.1.7 Sulfur Dioxide (SO₂) [326 IAC 7-1.1]
- D.1.8 Fuel Usage [326 IAC 2-8-4]
- D.1.9 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

- D.1.10 Testing Requirements [326 IAC 2-8-5(a)(1), (4)] [326 IAC 2-1.1-11]
- D.1.11 Sulfur Dioxide Emissions and Sulfur Content
- D.1.12 Particulate Matter (PM)

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

- D.1.13 Visible Emissions Notations
- D.1.14 Parametric Monitoring
- D.1.15 Baghouse Inspections
- D.1.16 Broken or Failed Bag Detection

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

- D.1.17 Record Keeping Requirements
- D.1.18 Reporting Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS

Batch Mix Asphalt Plant	30
--------------------------------	-----------

Construction Conditions

Emission Limitations and Standards [326 IAC 2-8-4(1)]

- D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-5-2]
- D.2.5 Cold-Mix (Stockpile Mix) VOC Usage [326 IAC 2-8-4]

Compliance Determination Requirements

D.2.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.7 Record Keeping Requirements

D.2.8 Reporting Requirements

SECTION D.2 FACILITY OPERATION CONDITIONS

Storage Tanks 32

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.2.1 Volatile Organic Compounds (VOCs) [326 IAC 12] [40 CFR 60.110b, Subpart Kb]

D.2.2 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

Compliance Determination Requirements

D.2.3 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.4 Record Keeping Requirements

Certification Form	33
Emergency/Deviation Form	34
Quarterly Report Form	36
Monthly Report Form	37
Quarterly Compliance Monitoring Report Form	38

SECTION A SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-8-3(b)]

The Permittee owns and operates a stationary batch mix asphalt plant.

Authorized individual:	Darwin Call
Source Address:	SR 114, Disko, IN
Mailing Address:	P.O. Box 284, Warsaw, IN 46580
Phone Number:	219-267-2422
SIC Code:	2951
Source Location Status:	Wabash
County Status:	Attainment for all criteria pollutants
Source Status:	Federally Enforceable State Operating Permit (FESOP) Minor Source, under PSD Rules; Minor Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-8-3(c)(3)]

This stationary source consists of the following emission units and pollution control devices:

- (a) one (1) hot mix asphalt batch plant, identified as unit S-1, with a maximum capacity of processing 160 tons of aggregates per hour, equipped with one (1) No. 2 distillate fuel oil fired aggregate dryer burner with a maximum rated capacity of 105 million (MM) British thermal units (Btu) per hour, and one (1) cyclone and one (1) baghouse in series for air pollution control, exhausting at one (1) stack, identified as EU-01;
- (b) one (1) 25,000 gallon asphalt cement storage tank, identified as Tank T1;
- (c) one (1) 12,000 gallon No. 2 fuel oil storage tank, identified as Tank T2;
- (d) cutback (stockpile mix) asphalt storage piles.

A.3 Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-8-3(c)(3)(I)]

This stationary source also includes the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Fuel oil-fired combustion sources with heat input equal to or less than two million (2,000,000) Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight,
- (b) Replacement or repair of electrostatic precipitators, bags in baghouses, and filters in other air filtration equipment,
- (c) Paved and unpaved roads and parking lots with public access,
- (d) Other categories with emissions below insignificant thresholds:
 - (1) Truck Loading

- (2) Conveyor transfers and batch drops
- (3) Aggregate storage

A.4 FESOP Applicability [326 IAC 2-8-2]

This stationary source, otherwise required to have a Part 70 permit as described in 326 IAC 2-7-2(a), has applied to the Indiana Department of Environmental Management (IDEM), Office of Air Management (OAM) for a Federally Enforceable State Operating Permit (FESOP).

A.5 Prior Permit Conditions

- (a) This permit shall be used as the primary document for determining compliance with applicable requirements established by previously issued permits.
- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, including any term or condition from a previously issued construction or operation permit, IDEM, OAM, shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued.

SECTION B GENERAL CONDITIONS

B.1 Permit No Defense [IC 13]

Indiana statutes from IC 13 and rules from 326 IAC, quoted in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a FESOP under 326 IAC 2-8.

B.2 Definitions [326 IAC 2-8-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2, and 326 IAC 2-7) shall prevail.

B.3 Permit Term [326 IAC 2-8-4(2)]

This permit is issued for a fixed term of five (5) years from the effective date, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3.

B.4 Enforceability [326 IAC 2-8-6]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA) and by citizens in accordance with the Clean Air Act.

B.5 Termination of Right to Operate [326 IAC 2-8-9] [326 IAC 2-8-3(h)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-8-3(h) and 326 IAC 2-8-9.

B.6 Severability [326 IAC 2-8-4(4)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.7 Property Rights or Exclusive Privilege [326 IAC 2-8-4(5)(D)]

This permit does not convey any property rights of any sort, or any exclusive privilege.

B.8 Duty to Supplement and Provide Information [326 IAC 2-8-3(f)] [326 IAC 2-8-4(5)(E)]

- (a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall furnish to IDEM, OAM, within a reasonable time, any information that IDEM, OAM, may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) Upon request, the Permittee shall also furnish to IDEM, OAM, copies of records required to be kept by this permit. The Permittee may include a claim of confidentiality in accordance with 326 IAC 17. If requested by IDEM, OAM, or the U.S. EPA, to furnish copies of requested records directly to U. S. EPA, then the Permittee must furnish record directly to the U. S. EPA. The Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.9 Compliance Order Issuance [326 IAC 2-8-5(b)]

IDEM, OAM may issue a compliance order to this Permittee upon discovery that this permit is in nonconformance with an applicable requirement. The order may require immediate compliance or contain a schedule for expeditious compliance with the applicable requirement.

B.10 Compliance with Permit Conditions [326 IAC 2-8-4(5)(A)] [326 IAC 2-8-4(5)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit, except those specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act and is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; and
 - (3) Denial of a permit renewal application.
- (b) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

B.11 Certification [326 IAC 2-8-3(d)] [326 IAC 2-8-4(3)(C)(i)] [326 IAC 2-8-5(1)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a authorized individual of truth, accuracy, and completeness. This certification, shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, on the attached Certification Form, with each submittal.
- (c) An authorized individual is defined at 326 IAC 2-1.1-1(1).

B.12 Annual Compliance Certification [326 IAC 2-8-5(a)(1)]

- (a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. The certification shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than April 15 of each year to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

- (b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification;
 - (2) The compliance status;
 - (3) Whether compliance was based on continuous or intermittent data;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-8-4(3); and
 - (5) Such other facts as specified in Sections D of this permit, IDEM, OAM, may require to determine the compliance status of the source.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.13 Preventive Maintenance Plan [326 IAC 1-6-3] [326 IAC 2-8-4(9)] [326 IAC 2-8-5(a)(1)]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) within ninety (90) days after issuance of this permit, including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If due to circumstances beyond its control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

The PMP and the PMP extension notification do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.

- (c) A copy of the PMPs shall be submitted to IDEM, OAM, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAM. IDEM, OAM, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

B.14 Emergency Provisions [326 IAC 2-8-12]

- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation, except as provided in 326 IAC 2-8-12.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a health-based or technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describes the following:
 - (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
 - (2) The permitted facility was at the time being properly operated;
 - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
 - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAM, within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone No.: 1-800-451-6027 (ask for Office of Air Management, Compliance Section) or,
Telephone No.: 317-233-5674 (ask for Compliance Section)
Facsimile No.: 317-233-5967

Failure to notify IDEM, OAM, by telephone or facsimile within four (4) daytime business hours after the beginning of the emergency, or after the emergency is discovered or reasonably should have been discovered, shall constitute a violation of 326 IAC 2-8 and any other applicable rules. [326 IAC 2-8-12(f)]

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted notice either in writing or facsimile, of the emergency to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-8-4(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;

(B) Any steps taken to mitigate the emissions; and

(C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

(6) The Permittee immediately took all reasonable steps to correct the emergency.

(c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.

(d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions) for sources subject to this rule after the effective date of this rule. This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.

(e) IDEM, OAM, may require that the Preventive Maintenance Plans required under 326 IAC 2-8-3(c)(6) be revised in response to an emergency.

(f) Failure to notify IDEM, OAM, by telephone or facsimile of an emergency lasting more than one (1) hour in compliance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-8 and any other applicable rules.

(g) Operations may continue during an emergency only if the following conditions are met:

(1) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

(2) If an emergency situation causes a deviation from a health-based limit, the Permittee may not continue to operate the affected emissions facilities unless:

(A) The Permittee immediately takes all reasonable steps to correct the emergency situation and to minimize emissions; and

(B) Continued operation of the facilities is necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw material of substantial economic value.

Any operations shall continue no longer than the minimum time required to prevent the situations identified in (g)(2)(B) of this condition.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-8-4(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provision), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management
Compliance Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

within ten (10) calendar days from the date of the discovery of the deviation, except for the failure to perform the monitoring or record the information required by the compliance monitoring provisions of Section D unless such failure exceeds 5% of the required data in any calendar quarter.

- (b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit or a rule. It does not include:
- (1) An excursion from compliance monitoring parameters as identified in Section D of this permit unless tied to an applicable rule or limit; or
 - (2) An emergency as defined in 326 IAC 2-7-1(12); or
 - (3) Failure to implement elements of the Preventive Maintenance Plan unless such failure has caused or contributed to a deviation.

A Permittee's failure to take the appropriate response step when an excursion of a compliance monitoring parameter has occurred is a deviation.

- (c) Written notification shall be submitted on the attached Emergency/Deviation Occurrence Reporting Form or its substantial equivalent. The notification does not need to be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (d) Proper notice submittal under 326 IAC 2-7-16 satisfies the requirement of this subsection.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination
[326 IAC 2-8-4(5)(C)] [326 IAC 2-8-7(a)] [326 IAC 2-8-8]

- (a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a FESOP modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any condition of this permit. [326 IAC 2-8-4(5)(C)] The notification by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAM determines any of the following:
- (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-8-8(a)]
- (c) Proceedings by IDEM, OAM, to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-8-8(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-8-8(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAM, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAM, may provide a shorter time period in the case of an emergency. [326 IAC 2-8-8(c)]

B.17 Permit Renewal [326 IAC 2-8-3(h)]

- (a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAM and shall include the information specified in 326 IAC 2-8-3. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, IN 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-8-3]

- (1) A timely renewal application is one that is:

- (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
- (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.

- (2) If IDEM, OAM upon receiving a timely and complete permit application, fails to issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect until the renewal permit has been issued or denied.

- (c) Right to Operate After Application for Renewal [326 IAC 2-8-9]

If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-8 until IDEM, OAM takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAM, any additional information identified as needed to process the application.

B.18 Permit Amendment or Revision [326 IAC 2-8-10] [326 IAC 2-8-11.1]

- (a) Permit amendments and revisions are governed by the requirements of 326 IAC 2-8-10 or 326 IAC 2-8-11.1 whenever the Permittee seeks to amend or modify this permit.

- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

Any such application should be certified by the "authorized individual" as defined by 326 IAC 2-1.1-1(1) only if a certification is required by the terms of the applicable rule.

- (c) The Permittee may implement the administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-10(b)(3)]

B.19 Operational Flexibility [326 IAC 2-8-15]

- (a) The Permittee may make any change or changes at this source that are described in 326 IAC 2-8-15(b) through (d), without prior permit revision, if each of the following conditions is met:
- (1) The changes are not modifications under any provision of Title I of the Clean Air Act;
 - (2) Any approval required by 326 IAC 2-8-11.1 has been obtained;
 - (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
 - (4) The Permittee notifies the:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V
Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J)
77 West Jackson Boulevard
Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and
 - (5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-8-15(b) through (d) and makes such records available, upon reasonable request, to public review.

Such records shall consist of all information required to be submitted to IDEM, OAM, in the notices specified in 326 IAC 2-8-15(b), (c)(1), and (d).
- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-8-15(a) and the following additional conditions:
- (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1.

- (c) Emission Trades [326 IAC 2-8-15(c)]
The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision, subject to the constraints of Section (a) of this condition and those in 326 IAC 2-8-15(c).
- (d) Alternative Operating Scenarios [326 IAC 2-8-15(d)]
The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-8-4(7). No prior notification of IDEM, OAM or U.S. EPA is required.

B.20 Permit Revision Requirement [326 IAC 2-8-11.1]

A modification, construction, or reconstruction is governed by the applicable provisions of 326 IAC 2-8-11.1.

B.21 Inspection and Entry [326 IAC 2-8-5(a)(2)]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAM, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a FESOP source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- (c) Inspect, at reasonable times, any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.
[326 IAC 2-8-5(a)(4)]

B.22 Transfer of Ownership or Operational Control [326 IAC 2-8-10]

- (a) The Permittee must comply with the requirements of 326 IAC 2-8-10 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management
Permits Branch, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-8-11(b)(3)]

B.23 Annual Fee Payment [326 IAC 2-8-4(6)] [326 IAC 2-8-16]

- (a) The Permittee shall pay annual fees to IDEM, OAM, within thirty (30) calendar days of receipt of a billing. If the Permittee does not receive a bill from IDEM, OAM the applicable fee is due April 1 of each year.
- (b) Failure to pay may result in administrative enforcement action, or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-0425 (ask for OAM, Technical Support and Modeling Section), to determine the appropriate permit fee.

B.24 Advanced Source Modification Approval [326 IAC 2-8-4(11)] [326 IAC 2-1.1-9]

- (a) The requirements to obtain a permit revision under 326 IAC 2-8-11.1 are satisfied by this permit for the proposed emission units, control equipment or insignificant activities in Sections A.2 and A.3.
- (b) Pursuant to 326 IAC 2-1.1-9 any permit authorizing construction may be revoked if failure to commence construction of the emission unit within eighteen (18) months from the date of issuance of the permit, or if during the construction of work is suspended for a continuous period of one (1) year or more.

SECTION C SOURCE OPERATION CONDITIONS

Entire Source

Emissions Limitations and Standards [326 IAC 2-8-4(1)]

C.1 Overall Source Limit [326 IAC 2-8]

The purpose of this permit is to limit this source's potential to emit to less than major source levels for the purpose of Section 502(a) of the Clean Air Act.

(a) Pursuant to 326 IAC 2-8:

- (1) The potential to emit any regulated pollutant from the entire source shall be limited to less than one-hundred (100) tons per twelve (12) consecutive month period. This limitation shall also make the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable;
- (2) The potential to emit any individual hazardous air pollutant (HAP) from the entire source shall be limited to less than ten (10) tons per twelve (12) consecutive month period; and
- (3) The potential to emit any combination of HAPs from the entire source shall be limited to less than twenty-five (25) tons per twelve (12) consecutive month period.

(b) This condition shall include all emission points at this source including those that are insignificant as defined in 326 IAC 2-7-1(21). The source shall be allowed to add insignificant activities not already listed in this permit, provided that the source's potential to emit does not exceed the above specified limits.

(c) Section D of this permit contains independently enforceable provisions to satisfy this requirement.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3(a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2(3)]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and in 326 IAC 9-1-2. 326 IAC 9-1-2 is not federally enforceable.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Fugitive Particulate Matter Emission Limitations [326 IAC 6-5]

Pursuant to 326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations), fugitive particulate matter emissions shall be controlled according to the plan submitted on April 25, 2000. The plan does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1). The plan consists of:

- (a) Limit vehicle traffic speed on plant roadways to 10 miles per hour; and
- (b) Wind erosion of aggregate storage piles shall be controlled using water spray.

C.7 Operation of Equipment [326 IAC 2-8-5(a)(4)]

Except as otherwise provided in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

C.8 Stack Height [326 IAC 1-7]

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted.

C.9 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61.140]

- (a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.
- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management
Asbestos Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

The notifications do not require a certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (e) **Procedures for Asbestos Emission Control**
The Permittee shall comply with the applicable emission control procedures in 326 IAC 14-10-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-4 emission control requirements are applicable for any removal or disturbance of RACM greater than three (3) linear feet on pipes or three (3) square feet on any other facility components or a total of at least 0.75 cubic feet on all facility components.
- (f) **Indiana Accredited Asbestos Inspector**
The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator, prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to thoroughly inspect the affected portion of the facility for the presence of asbestos. The requirement that the inspector be accredited is federally enforceable.

Testing Requirements [326 IAC 2-8-4(3)]

C.10 Performance Testing [326 IAC 3-6]

- (a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAM.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (b) The Permittee shall notify IDEM, OAM of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAM within forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAM, , if the source submits to IDEM, OAM, a reasonable written explanation within five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.11 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.12 Compliance Monitoring [326 IAC 2-8-4(3)] [326 IAC 2-8-5(a)(1)]

All monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P.O. Box 6015
Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule with full justification of the reasons for inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Compliance monitoring for new emission units or emission units added through a permit revision shall be implemented when operation begins.

C.13 Monitoring Methods [326 IAC 3]

Any monitoring or testing performed required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, or other approved methods as specified in this permit.

C.14 Pressure Gauge Specifications

Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and be accurate within plus or minus two percent ($\pm 2\%$) of full scale reading.

Corrective Actions and Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

C.15 Risk Management Plan [326 IAC 2-8-4] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68 by the date provided in 40 CFR 68.10(a); or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP); and
- (c) A verification to IDEM, OAM, that a RMP or a revised plan was prepared and submitted as required by 40 CFR 68.

All documents submitted pursuant to this condition shall include the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

C.16 Compliance Monitoring Plan - Failure to Take Response Steps [326 IAC 2-8-4] [326 IAC 2-8-5]

- (a) The Permittee is required to implement a compliance monitoring plan to ensure that reasonable information is available to evaluate its continuous compliance with applicable requirements. The compliance monitoring plan can be either an entirely new document, consist in whole information contained in other documents, or consist of a combination of new information and information contained in other documents. If the compliance monitoring plan incorporates by reference information contained in other documents, the Permittee shall identify as part of the compliance monitoring plan the documents in which the information is found. The elements of the compliance monitoring plan are:
- (1) This condition;
 - (2) The Compliance Determination Requirements in Section D of this permit;
 - (3) The Compliance Monitoring Requirements in Section D of this permit;
 - (4) The Record Keeping and Reporting Requirements in Section C (Monitoring Data Availability, General Record Keeping Requirements, and General Reporting Requirements) and in Section D of this permit; and
 - (5) A Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. CRP's shall be submitted to IDEM, OAM upon request and shall be subject to review and approval by IDEM, OAM. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee and maintained on site, and is comprised of:
 - (A) Reasonable response steps that may be implemented in the event that compliance related information indicates that a response step is needed pursuant to the requirements of Section D of this permit; and
 - (B) A time schedule for taking reasonable response steps including a schedule for devising additional response steps for situations that may not have been predicted.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition. Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) Upon investigation of a compliance monitoring excursion, the Permittee is excused from taking further response steps for any of the following reasons:
- (1) A false reading occurs due to the malfunction of the monitoring equipment. This shall be an excuse from taking further response steps providing that prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for an administrative amendment to the permit, and such request has not been denied; or
 - (3) An automatic measurement was taken when the process was not operating; or
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.

- (d) Records shall be kept of all instances in which the compliance related information was not met and of all response steps taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (e) All monitoring required in Section D shall be performed at all times the equipment is operating. If monitoring is required by Section D and the equipment is not operating, then the Permittee may record the fact that the equipment is not operating or perform the required monitoring.
- (f) If for reasons beyond its control, the Permittee fails to perform the monitoring and record keeping as required by Section D, then the reasons for this must be recorded.
 - (1) At its discretion, IDEM may excuse such failure providing adequate justification is documented and such failures do not exceed five percent of the operating time in any quarter.
 - (2) Temporary, unscheduled unavailability of qualified staff shall be considered a valid reason for failure to perform the monitoring or record keeping requirements in Section D.

**C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-8-4]
[326 IAC 2-8-5]**

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate corrective actions. The Permittee shall submit a description of these corrective actions to IDEM, OAM, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the corrective actions are being implemented.
- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAM that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAM may extend the retesting deadline.
- (c) IDEM, OAM reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)]

C.18 General Record Keeping Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-5]

- (a) Records of all required monitoring data and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Records of required monitoring information shall include, where applicable:

- (1) The date, place, and time of sampling or measurements;
 - (2) The dates analyses were performed;
 - (3) The company or entity performing the analyses;
 - (4) The analytic techniques or methods used;
 - (5) The results of such analyses; and
 - (6) The operating conditions existing at the time of sampling or measurement.
- (c) Support information shall include, where applicable:
- (1) Copies of all reports required by this permit;
 - (2) All original strip chart recordings for continuous monitoring instrumentation;
 - (3) All calibration and maintenance records;
 - (4) Records of preventive maintenance.
- (d) All record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.19 General Reporting Requirements [326 IAC 2-8-4(3)(C)] [326 IAC 2-1.1-11]

- (a) To affirm that the source has met all the compliance monitoring requirements stated in this permit the source shall submit a Quarterly Compliance Monitoring Report. Any deviation from the requirements and the date(s) of each deviation must be reported. The Compliance Monitoring Report shall include the certification by the "authorized individual" as defined by 326 IAC2-1.1-1(1).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management
Compliance Data Section, Office of Air Management
100 North Senate Avenue, P. O. Box 6015
Indianapolis, Indiana 46206-6015
- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAM, on or before the date it is due.
- (d) Unless otherwise specified in this permit, any quarterly report required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. The report does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).
- (e) All instances of deviations as described in Section B- Deviations from Permit Requirements Conditions must be clearly identified in such reports. The Emergency/Deviation Occurrence Report does not require the certification by the "authorized individual" as defined by 326 IAC 2-1.1-1(1).

- (f) Any corrective actions or response steps taken as a result of each deviation must be clearly identified in such reports.
- (g) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

Stratospheric Ozone Protection

C.20 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair or disposal must comply with the required practices pursuant to 40 CFR 82.156
- (b) Equipment used during the maintenance, service, repair or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

- (a) one (1) hot mix asphalt batch plant, identified as unit S-1, with a maximum capacity of processing 160 tons of aggregates per hour, equipped with one (1) No. 2 distillate fuel oil fired aggregate dryer burner with a maximum rated capacity of 105 million (MM) British thermal units (Btu) per hour, and one (1) cyclone and one (1) baghouse in series for air pollution control, exhausting at one (1) stack, identified as EU-01.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 326 IAC 2-8-11.1, WITH CONDITIONS LISTED BELOW.

Construction Conditions

General Construction Conditions

- D.1.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

Effective Date of the Permit

- D.1.2 Pursuant to IC 13-15-5-3, this section of this permit becomes effective upon its issuance.
- D.1.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for revisions pursuant to 326 IAC 2.

Operation Conditions

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.1.4 Particulate Matter (PM) [326 IAC 6-3-2] [326 IAC 12] [40 CFR 60.90, Subpart I]

- (a) Pursuant to 326 IAC 6-3-2 (Process Operations), the particulate matter emissions from the mixing and drying operation shall be limited to 56.12 pounds per hour.
- (b) Pursuant to 326 IAC 12, (40 CFR Part 60.90, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the particulate matter emissions from the mixing and drying operations shall be limited to 0.04 grains per dry standard cubic foot (gr/dscf). This is equivalent to a particulate matter emission rate of 9.32 pounds per hour. This limit will also render 326 IAC 2-2 (Prevention of Significant Deterioration (PSD)) not applicable.

Compliance with the PM emission limit pursuant to 326 IAC 12, 40 CFR Part 60.90, Subpart I will also satisfy the PM emission limit pursuant to 326 IAC 6-3-2.

D.1.5 Opacity [326 IAC 12] [40 CFR 60.90, Subpart I]

Pursuant to 326 IAC 12, (40 CFR Part 60.92, Subpart I) "Standards of Performance for Hot Mix Asphalt Facilities", the mixing and drying operations shall not discharge or cause the discharge into the atmosphere any gases which exhibit 20% opacity or greater.

D.1.6 Particulate Matter 10 Microns (PM-10) [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4, particulate matter 10 microns emissions from the aggregate mixing and drying operation shall not exceed 20.92 pounds per hour, including both filterable and condensable fractions. Compliance with this limit will satisfy 326 IAC 2-8-4. Therefore, the Part 70 rules (326 IAC 2-7) do not apply.

D.1.7 Sulfur Dioxide (SO₂) [326 IAC 7-1.1]

Pursuant to 326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations), sulfur dioxide emissions from the 105.0 million Btu per hour burner for the aggregate dryer shall be limited to 0.5 pounds per million Btu heat input or a sulfur content of less than or equal to 0.5% when using distillate oil.

D.1.8 Fuel Usage [326 IAC 2-8-4]

Pursuant to 326 IAC 2-8-4(1), the input of No. 2 fuel oil with a maximum sulfur content of 0.5% to the 105.0 MMBtu per hour burner for the aggregate dryer shall be limited to 2,828,571 U.S. gallons per twelve (12) consecutive month period, rolled on a monthly basis, so that SO₂ emissions are limited below 100 tons per year.

Therefore, the requirements of 326 IAC 2-7 will not apply.

D.1.9 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Determination Requirements

D.1.10 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

During the period between 30 and 36 months after issuance of this permit, the Permittee shall perform PM and PM-10 testing utilizing Methods 5 or 17 (40 CFR 60, Appendix A) for PM and Methods 201 or 201A and 202 (40 CFR 51, Appendix M) for PM-10, or other methods as approved by the Commissioner. This test shall be repeated at least once every five (5) years from the date of this valid compliance demonstration. PM-10 includes filterable and condensable PM-10. In addition to these requirements, IDEM may require compliance testing when necessary to determine if the facility is in compliance.

D.1.11 Sulfur Dioxide Emissions and Sulfur Content

Compliance shall be determined utilizing one of the following options.

- (a) Pursuant to 326 IAC 3-7-4, the Permittee shall demonstrate that the No. 2 distillate fuel oil sulfur content does not exceed 0.5% by weight by:
 - (1) Providing vendor analysis of fuel delivered, if accompanied by a certification;
 - (2) Analyzing the oil sample to determine the sulfur content of the oil via the procedures in 40 CFR 60, Appendix A, Method 19.
 - (A) Oil samples may be collected from the fuel tank immediately after the fuel tank is filled and before any oil is combusted; and
 - (B) If a partially empty fuel tank is refilled, a new sample and analysis would be required upon filling; or
- (b) Compliance may also be determined by conducting a stack test for sulfur dioxide emissions from the 105.0 MMBtu per hour burner for the aggregate dryer, using 40 CFR 60, Appendix A, Method 6 in accordance with the procedures in 326 IAC 3-6.

A determination of noncompliance pursuant to either of the methods specified in (a) or (b) above shall not be refuted by evidence of compliance pursuant to the other method.

D.1.12 Particulate Matter (PM)

The cyclone and baghouse for PM control shall be in operation at all times when the aggregate dryer is in operation.

Compliance Monitoring Requirements [326 IAC 2-8-4] [326 IAC 2-8-5(a)(1)]

D.1.13 Visible Emissions Notations

- (a) Visible emission notations of the aggregate dryer baghouse stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.

D.1.14 Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the aggregate dryer, at least once daily when the aggregate dryer is in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 5.0 and 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months.

D.1.15 Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the aggregate dryer when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective bags shall be replaced.

D.1.16 Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (a) The affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).
- (b) For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.1.17 Record Keeping Requirements

- (a) To document compliance with Condition D.1.13, the Permittee shall maintain records of visible emission notations of the aggregate dryer baghouse stack exhaust once per shift.
- (b) To document compliance with Condition D.1.14, the Permittee shall maintain the following:
 - (1) Daily records of the following operational parameters during normal operation when venting to the atmosphere:
 - (A) Inlet and outlet differential static pressure; and
 - (B) Cleaning cycle: frequency and differential pressure.
 - (2) Documentation of all response steps implemented, per event .
 - (3) Operation and preventive maintenance logs, including work purchases orders, shall be maintained.
 - (4) Quality Assurance/Quality Control (QA/QC) procedures.
 - (5) Operator standard operating procedures (SOP).
 - (6) Manufacturer's specifications or its equivalent.
 - (7) Equipment "troubleshooting" contingency plan.
 - (8) Documentation of the dates vents are redirected.
- (c) To document compliance with Condition D.1.15, the Permittee shall maintain records of the results of the inspections required under Condition D.1.15 and the dates the vents are redirected.
- (d) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.1.18 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.1.8 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.2 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]

(d) cutback (stockpile mix) asphalt storage piles.

THIS SECTION OF THE PERMIT IS BEING ISSUED UNDER THE PROVISIONS OF 326 IAC 2-1 AND 326 IAC 2-8-11.1, WITH CONDITIONS LISTED BELOW.

Construction Conditions

General Construction Conditions

D.2.1 This permit to construct does not relieve the Permittee of the responsibility to comply with the provisions of the Indiana Environmental Management Law (IC 13-11 through 13-20; 13-22 through 13-25; and 13-30), the Air Pollution Control Law (IC 13-17) and the rules promulgated thereunder, as well as other applicable local, state, and federal requirements.

Effective Date of the Permit

D.2.2 Pursuant to IC 13-15-5-3, this section of this permit becomes effective upon its issuance.

D.2.3 All requirements of these construction conditions shall remain in effect unless modified in a manner consistent with procedures established for revisions pursuant to 326 IAC 2.

Operation Conditions

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.2.4 Volatile Organic Compounds (VOC) [326 IAC 8-5-2]

Pursuant to 326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving), the use of cutback asphalt or asphalt emulsion shall not contain more than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:

- 1) penetrating prime coating
- 2) stockpile storage
- 3) application during the months of November, December, January, February and March.

D.2.5 Cold-Mix (Stockpile Mix) VOC Usage [326 IAC 2-8-4]

The VOC usage in the production of cutback (stockpile mix) asphalt shall be limited to 94.29 tons per twelve (12) consecutive month period, rolled on a monthly basis. The total for each month shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous eleven (11) months. This is equivalent to 134.70 tons of diluent used per twelve (12) consecutive month period in the production of cutback (stockpile mix) asphalt based on 70% volatilization. During the first twelve (12) consecutive months of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated days of operation shall not exceed 11.22 tons per month. Therefore, the requirements of 326 IAC 2-7 will not apply.

Compliance Determination Requirements

D.2.6 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the VOC limit specified in Condition D.2.5 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

Record Keeping and Reporting Requirement [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.2.7 Record Keeping Requirements

- (b) To document compliance with Condition D.2.5, the Permittee shall maintain records in accordance with (1) through (4) below. Records maintained for (1) through (4) shall be taken monthly and shall be complete and sufficient to establish compliance with the VOC usage limits and/or the VOC emission limits established in Condition D.2.5.
- (1) diluent used in production of cutback asphalt per day;
 - (2) amount of diluent used last 365 days;
 - (3) type of liquid binder used; and
 - (4) percent diluent (oil distillate) in liquid binder.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

D.2.8 Reporting Requirements

A quarterly summary of the information to document compliance with Condition D.2.5 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported.

SECTION D.3 FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-8-4(10)]:

- (c) one (1) 25,000 gallon asphalt storage tank, identified as Tank T1; and
 - (d) one (1) 12,000 gallon No. 2 fuel oil storage tank, identified as Tank T2.
- (The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-8-4(1)]

D.3.1 Volatile Organic Compounds (VOCs) [326 IAC 12] [40 CFR 60.110b, Subpart Kb]

- (a) Pursuant to 40 CFR Part 60.110b, Subpart Kb (Standards of Performance for Volatile Organic Liquid Storage Vessels), the one (1) 25,000 gallon asphalt storage tank, identified as Tank T1, with a vapor pressure of less than 15.0 kPa, is subject to 40 CFR Part 60.116b, paragraphs (a), (b), and (c) which require record keeping.
- (b) Pursuant to 40 CFR Part 60.110b, Subpart Kb (Standards of Performance for Volatile Organic Liquid Storage Vessels), the one (1) 12,000 gallon No. 2 fuel oil storage tank, identified as Tank T2, with a storage capacity less than 75 cubic meters, are subject to 40 CFR Part 60.116b, paragraphs (a) and (b), which require record keeping.

D.3.2 Preventive Maintenance Plan [326 IAC 2-8-4(9)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for these facilities and any control devices.

Compliance Determination Requirements

D.3.3 Testing Requirements [326 IAC 2-8-5(a)(1), (4)][326 IAC 2-1.1-11]

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance with the VOC limit specified in Condition D.2.1 shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

Record Keeping and Reporting Requirements [326 IAC 2-8-4(3)] [326 IAC 2-8-16]

D.3.4 Record Keeping Requirements

- (a) To document compliance with Condition D.2.1, the Permittee shall maintain permanent records at the source in accordance with (1) through (3) below:
 - (1) the dimension of each storage vessel;
 - (2) an analysis showing the capacity of each storage vessel; and
 - (3) the true vapor pressure of each VOC stored in the one (1) 25,000 gallon asphalt storage tank, indicating that the maximum true vapor pressure of VOC is less than 15.0 kPa.
- (b) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
CERTIFICATION**

Source Name: Ranger Materials Corporation
Source Address: SR 114, Disko, IN
Mailing Address: P.O. Box 284, Warsaw, IN 46580
FESOP No.: F169-12210-00061

This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.

Please check what document is being certified:

- 9 Annual Compliance Certification Letter
- 9 Test Result (specify) _____
- 9 Report (specify) _____
- 9 Notification (specify) _____
- 9 Affidavit (specify) _____
- 9 Other (specify) _____

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION
P.O. Box 6015
100 North Senate Avenue
Indianapolis, Indiana 46206-6015
Phone: 317-233-5674
Fax: 317-233-5967**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
EMERGENCY/DEVIATION OCCURRENCE REPORT**

Source Name: Ranger Materials Corporation
Source Address: SR 114, Disko, IN
Mailing Address: P.O. Box 284, Warsaw, IN 46580
FESOP No.: F169-12210-00061

This form consists of 2 pages

Page 1 of 2

Check either No. 1 or No.2

9 1. This is an emergency as defined in 326 IAC 2-7-1(12)
CThe Permittee must notify the Office of Air Management (OAM), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
CThe Permittee must submit notice in writing or by facsimile within two (2) days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16

9 2. This is a deviation, reportable per 326 IAC 2-8-4(3)(C)
CThe Permittee must submit notice in writing within ten (10) calendar days

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:

Control Equipment:

Permit Condition or Operation Limitation in Permit:

Description of the Emergency/Deviation:

Describe the cause of the Emergency/Deviation:

If any of the following are not applicable, mark N/A

Page 2 of 2

Date/Time Emergency/Deviation started:
Date/Time Emergency/Deviation was corrected:
Was the facility being properly operated at the time of the emergency/deviation? Y N Describe:
Type of Pollutants Emitted: TSP, PM-10, SO ₂ , VOC, NO _x , CO, Pb, other:
Estimated amount of pollutant(s) emitted during emergency/deviation:
Describe the steps taken to mitigate the problem:
Describe the corrective actions/response steps taken:
Describe the measures taken to minimize emissions:
If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by: _____
Title / Position: _____
Date: _____
Phone: _____

A certification is not required for this report.

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

FESOP Quarterly Report

Source Name: Ranger Materials Corporation
Source Address: SR 114, Disko, IN
Mailing Address: P.O. Box 284, Warsaw, IN 46580
FESOP No.: F169-12210-00061
Facility: batch mix dryer
Parameter: Sulfur Dioxide (SO₂)
Limit: The input of No. 2 fuel oil with a maximum sulfur content of 0.5% to the 105.0 MMBtu per hour burner for the aggregate dryer shall be limited to 2,828,571 U.S. gallons per twelve (12) consecutive month period, rolled on a monthly basis, so that SO₂ emissions are limited below 100 tons per year.

YEAR: _____

Month	Fuel Type	Column 1	Column 2	Column 1 + Column 2
		No. 2 Residual Fuel Oil Usage This Month	No. 2 Residual Fuel Oil Usage Previous 11 Months	12 Month Total No. 2 Residual Fuel Oil Usage

9 No deviation occurred in this quarter.

9 Deviation/s occurred in this quarter.

Deviation has been reported on: _____

Submitted by: _____

Title / Position: _____

Signature: _____

Date: _____

Phone: _____

A certification is not required for this report.

FESOP Monthly Report

Source Name: Ranger Materials Corporation
Source Address: SR 114, Disko, IN
Mailing Address: P.O. Box 284, Warsaw, IN 46580
FESOP No.: F169-12210-00061
Facility: cold-mix (stockpile mix) asphalt storage piles
Parameter: volatile organic compounds (VOC)
Limit: The VOC usage in the production of cutback (stockpile mix) asphalt shall be limited to 94.29 tons per twelve (12) consecutive month period, rolled on a monthly basis. The total for each month shall not exceed the difference between the annual usage limit minus the sum of actual usage from the previous eleven (11) months. This is equivalent to 134.70 tons of diluent used per twelve (12) consecutive month period in the production of cutback (stockpile mix) asphalt based on 70% volatilization. During the first twelve (12) consecutive months of operation under this permit, the usage of diluent shall be limited such that the total usage divided by the accumulated days of operation shall not exceed 11.22 tons per month.

YEAR: _____

Month	Column 1	Column 2	Column 1 + Column 2
	Diluent Usage This Month (tons)	Diluent Usage Previous 11 Months (tons)	12 Month Total Diluent Usage (tons)
Month 1			
Month 2			
Month 3			

9 No deviation occurred in this month.

9 Deviation/s occurred in this month.

Deviation has been reported on: _____

Submitted by: _____
Title/Position: _____
Signature: _____
Date: _____
Phone: _____

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
OFFICE OF AIR MANAGEMENT
COMPLIANCE DATA SECTION**

**FEDERALLY ENFORCEABLE STATE OPERATING PERMIT (FESOP)
QUARTERLY COMPLIANCE MONITORING REPORT**

Source Name: Ranger Materials Corporation
Source Address: SR 114, Disko, IN
Mailing Address: P.O. Box 284, Warsaw, IN 46580
FESOP No.: F169-12210-00061

Months: _____ **to** _____ **Year:** _____

This report is an affirmation that the source has met all the compliance monitoring requirements stated in this permit. This report shall be submitted quarterly based on a calendar year. Any deviation from the compliance monitoring requirements and the date(s) of each deviation must be reported. Additional pages may be attached if necessary. This form can be supplemented by attaching the Emergency/Deviation Occurrence Report. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period".

9 NO DEVIATIONS OCCURRED THIS REPORTING PERIOD.

9 THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD.

Compliance Monitoring Requirement (eg. Permit Condition D.1.3)	Number of Deviations	Date of each Deviation

Form Completed By: _____
Title/Position: _____
Date: _____
Phone: _____

Attach a signed certification to complete this report.

Mail to: Permit Administration & Development Section
Office Of Air Management
100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015

Ranger Materials Corporation
SR 114
Disko, IN

Affidavit of Construction

I, _____, being duly sworn upon my oath, depose and say:
(Name of the Authorized Representative)

1. I live in _____ County, Indiana and being of sound mind and over twenty-one (21) years of age, I am competent to give this affidavit.
2. I hold the position of _____ for _____.
(Title) (Company Name)
3. By virtue of my position with _____, I have personal
(Company Name)
knowledge of the representations contained in this affidavit and am authorized to make
these representations on behalf of _____.
(Company Name)
4. I hereby certify that Ranger Materials Corporation, SR 114, Disko, IN, has constructed the stationary batch mix asphalt plant in conformity with the requirements and intent of the construction permit application received by the Office of Air Management on April 25, 2000 and as permitted pursuant to **New Source Construction Permit and Federally Enforceable State Operating Permit No. F169-12210-00061** issued on _____

Further Affiant said not.

I affirm under penalties of perjury that the representations contained in this affidavit are true, to the best of my information and belief.

Signature

Date

STATE OF INDIANA)
)SS

COUNTY OF _____)

Subscribed and sworn to me, a notary public in and for _____ County and State of
Indiana on this _____ day of _____, 20 _____.
My Commission expires: _____

Signature

Name (typed or printed)

**Indiana Department of Environmental Management
Office of Air Management**

Technical Support Document (TSD) for a
New Source Construction Permit and
Federally Enforceable State Operating Permit (FESOP)

Source Background and Description

Source Name:	Ranger Materials Corporation
Source Location:	SR 114, Disko, IN
County:	Wabash
SIC Code:	2951
Operation Permit No.:	F169-12210-00061
Permit Reviewer:	Phillip Ritz/EVP

The Office of Air Management (OAM) has reviewed a FESOP application from Ranger Materials Corporation relating to the construction and operation of a stationary batch mix asphalt plant.

New Emission Units and Pollution Control Equipment Receiving Advanced Source Modification Approval

The application includes information relating to the prior approval for the construction and operation of the following equipment pursuant to 326 IAC 2-8-4(11):

- (a) one (1) hot mix asphalt batch plant, identified as unit S-1, with a maximum capacity of processing 160 tons of aggregates per hour, equipped with one (1) No. 2 distillate fuel oil fired aggregate dryer burner with a maximum rated capacity of 105 million (MM) British thermal units (Btu) per hour, and one (1) cyclone and one (1) baghouse in series for air pollution control, exhausting at one (1) stack, identified as EU-01;
- (b) one (1) 25,000 gallon asphalt cement storage tank, identified as Tank T1;
- (c) one (1) 12,000 gallon No. 2 fuel oil storage tank, identified as Tank T2;
- (d) cutback (stockpile mix) asphalt storage piles.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Fuel oil-fired combustion sources with heat input equal to or less than two million (2,000,000) Btu per hour and firing fuel containing less than five-tenths (0.5) percent sulfur by weight,
- (b) Replacement or repair of electrostatic precipitators, bags in baghouses, and filters in other air filtration equipment,
- (c) Paved and unpaved roads and parking lots with public access,
- (d) Other categories with emissions below insignificant thresholds:
 - (1) Truck Loading
 - (2) Conveyor transfers and batch drops
 - (3) Aggregate storage

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the FESOP be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete FESOP application for the purposes of this review was received on April 25, 2000.

Emission Calculations

See Appendix A of this document for detailed emissions calculations (Appendix A, pages 1 through 8)

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	22,453.52

PM-10	3,162.72
SO ₂	229.95
VOC	13,740.79
CO	16.43
NO _x	65.70

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential To Emit (tons/year)
Acetaldehyde	0.91
Acrolein	0.02
Arsenic	0.00
Benzene	0.29
Beryllium	0.00
Cadmium	0.00
Chromium	0.00
Ethylbenzene	0.27
Formaldehyde	1.68
Lead	0.00
Manganese	0.00
Mercury	0.00
Methyl Ethyl Ketone	0.01
Nickel	0.00
Propionaldehyde	0.09
Quinone	0.11
Selenium	0.01
Toluene	0.53
Total POM	0.41
Xylene	0.11
TOTAL	4.45

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of PM-10, VOC and SO₂ are equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories under 326 IAC 2-2 and since there are applicable New Source Performance Standards that were in effect on August 7, 1980, the fugitive emissions are counted toward determination of PSD and Emission Offset applicability.

Actual Emissions

No previous emission data has been received from the source.

Potential to Emit After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Federally Enforceable State Operating Permit.

	Limited Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO ₂	VOC	CO	NO _x	HAPs
Aggregate Heating	40.84	91.62	99.00	4.70	7.07	28.29	4.42
Aggregate Drying	6.87	1.54	0.00	0.00	0.00	0.00	0.00
Cutback VOC storage	0.00	0.00	0.00	94.29	0.00	0.00	0.00
Conveying/handling	6.54	0.65	0.00	0.00	0.00	0.00	0.00
Unpaved Road	14.74	5.16	0.00	0.00	0.00	0.00	0.00
Storage	0.08	0.03	0.00	0.00	0.00	0.00	0.00
Total Emissions	69.07	99.00	99.00	99.00	7.07	28.29	4.42

County Attainment Status

The source is located in Wabash County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) and oxides of nitrogen (NO_x) are precursors for the formation of ozone. Therefore, VOC and NO_x emissions are considered when evaluating the rule applicability relating to the ozone standards. Wabash County has been designated as attainment or unclassifiable for ozone.

Federal Rule Applicability

- (a) This source is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR 60.90, Subpart I) because it meets the definition of a hot mix asphalt facility pursuant to the rule and it was constructed after June 11, 1973. This rule limits particulate matter emissions to 0.04 grains per dry standard cubic foot (gr/dscf) and also limits visible emissions to 20% opacity. This is equivalent to a particulate matter emission rate of 9.32 pounds per hour. The source will comply with this rule by using a baghouse to limit particulate matter emissions to less than 0.03 gr/dscf (see Appendix A, page 14 of 14, for detailed calculations).
- (b) The one (1) 25,000 gallon asphalt storage tank and is subject to the requirements of the New Source Performance Standard, 326 IAC 12, (40 CFR 60.110b, Subpart Kb) because the tank was constructed after July 23, 1984, and has a storage capacity greater than 40 cubic meters. However, since the tank has a storage capacity greater than 75 cubic meters but less than 151 cubic meters, and the liquid stored in the tank has a maximum true vapor pressure of less than 15.0 kPa, the tank is subject to only 40 CFR Part 60.116b, paragraphs (a), (b), and (c) which require record keeping.

- (c) The one (1) 12,000 gallon No. 2 fuel oil storage tank is subject to the New Source Performance Standard, 326 IAC 12, (40 CFR Part 60.11b, Subpart Kb) "Standards of Performance for Volatile Organic Liquid Storage Vessels" since it was constructed after July 23, 1984, and has a storage capacity of greater than 40 cubic meters. However, since the tank has a storage capacity less than 75 cubic meters, the tank is subject to only 40 CFR Part 60.116b, paragraphs (a) and (b) which require record keeping.
- (d) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.

State Rule Applicability - Entire Source

326 IAC 1-6-3 (Preventive Maintenance Plan)

The source has submitted a Preventive Maintenance Plan (PMP) on April 25, 2000. This PMP has been verified to fulfill the requirements of 326 IAC 1-6-3 (Preventive Maintenance Plan).

326 IAC 2-2 (Prevention of Significant Deterioration)

This source is not subject to 326 IAC 2-2 (PSD) as it has accepted federally enforceable operation conditions which limit emissions of PM-10 to below 250 tons per 12-month period. Also, controlled PM emissions are below 250 tons per year. Therefore, pursuant to 326 IAC 2-2, and 40 CFR 52.21, the PSD requirements do not apply.

326 IAC 2-6 (Emission Reporting)

This source is located in Wabash County and the potential to emit all criteria pollutants is less than one hundred tons per year. Therefore, 326 IAC 2-6 does not apply.

326 IAC 2-8-4 (FESOP)

This source is subject to 326 IAC 2-8-4 (FESOP). Pursuant to this rule, the usage of No. 2 residual fuel oil, with a maximum sulfur content of 0.49% in the aggregate dryer burner shall be limited to 2,828,571 U.S. gallons per twelve (12) consecutive month period, rolled on a monthly basis, so that SO₂ emissions are limited below 100 tons per year. The VOC usage in the production of cutback (stockpile mix) asphalt shall be limited to 94.29 tons per twelve (12) consecutive month period, rolled on a monthly basis, so that VOC emissions are limited below 100 tons per year. This is equivalent to 134.70 tons of diluent used per twelve (12) consecutive month period in the production of cutback (stockpile mix) asphalt based on 70% volatilization. Also, PM-10 emissions from the aggregate dryer shall be limited to 20.92 pounds per hour so that source-wide PM-10 emissions are limited below 100 tons per year. The cyclone and baghouse controlling the aggregate dryer particulate emissions shall be in operation at all times when the aggregate dryer is in operation and total PM-10 emissions shall not exceed 21.27 pounds per hour or 93.16 tons per year (99 tons/yr - 5.84 tons/yr from other sources).

326 IAC 5-1 (Visible Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

326 IAC 6-4 (Fugitive Dust Emissions)

This source is subject to 326 IAC 6-4 for fugitive dust emissions. Pursuant to 326 IAC 6-4 (Fugitive Dust Emissions), fugitive dust shall not be visible crossing the boundary or property line of a source. Observances of visible emissions crossing property lines may be refuted by factual data expressed in 326 IAC 6-4-2(1), (2) or (3).

326 IAC 6-5 (Fugitive Particulate Matter Emission Limitations)

This source is subject to 326 IAC 6-5 for fugitive particulate matter emissions. Pursuant to 326 IAC 6-5, for any new source which has not received all the necessary preconstruction approvals before December 13, 1985, a fugitive dust control plan must be submitted, reviewed and approved. The fugitive dust control plan for this source includes the following:

- (a) Limit vehicle traffic speed on plant roadways to 10 miles per hour; and
- (b) Wind erosion of aggregate storage piles shall be controlled using water spray.

State Rule Applicability - Individual Facilities

326 IAC 6-3-2 (Process Operations)

Pursuant to 326 IAC 6-3-2 the particulate matter (PM) from the hot mix asphalt batch plant shall be limited by the following:

Interpolation and extrapolation of the data for the process weight rate in excess of sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 55.0 P^{0.11} - 40 \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

$$56.12 = 55.0 (160)^{0.11} - 40 \quad \text{where } E = 56.12 \text{ pounds per hour} \\ P = 160 \text{ tons per hour}$$

According to the emission calculations, when operating with the cyclone and baghouse for particulate matter control the one (1) hot mix asphalt batch plant, identified as unit S-1, has a potential to emit (PTE) PM of 1.57 pounds per hour (equivalent to 6.87 tons per year), and the source is in compliance with the requirement. (See emission calculations, page 5 of 8).

326 IAC 7-1.1 (Sulfur Dioxide Emission Limitations)

The sulfur dioxide emissions from the 105.0 MMBtu/hr dryer burning distillate oil shall be limited to 0.5 lb/MMBtu heat input. This equates to a distillate fuel oil sulfur content limit of 0.5%. The source will comply with this rule by using No. 2 distillate fuel oil with a sulfur content of 0.5% or less in the dryer (See Appendix A, Page 5 of 8 for detailed calculations).

326 IAC 7-2-1 (Sulfur Dioxide Reporting Requirements)

This source is subject to 326 IAC 7-2-1 (Reporting Requirements). This rule requires the source to submit to the Office of Air Management upon request records of sulfur content, heat content, fuel consumption, and sulfur dioxide emission rates based on a calendar-month average.

326 IAC 8-5-2 (Miscellaneous Operations: Asphalt Paving)

No person shall cause or allow the use of cutback asphalt or asphalt emulsion containing more

than seven percent (7%) oil distillate by volume of emulsion for any paving application except the following purposes:

- 1) penetrating prime coating
- 2) stockpile storage
- 3) application during the months of November, December, January, February and March.

The source is in compliance with 326 IAC 8-5-2.

Testing Requirements

The one (1) hot mix asphalt batch plant, identified as unit S-1, utilizes a control device to comply with PM-10 emission limitations and the allowable PM-10 emissions are over 10 pounds per hour. Therefore PM-10 testing is required for this emission unit. The PM emissions are subject to New Source Performance Standard, 326 IAC 12, (40 CFR 60.90, Subpart I), therefore, PM testing is required for this emission unit.

Compliance Requirements

Permits issued under 326 IAC 2-8 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAM, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-8-4. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this source are as follows:

1. The aggregate dryer has applicable compliance monitoring conditions as specified below:
 - (a) Visible emission notations of the aggregate dryer baghouse stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal. For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time. In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions. A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed.
 - (b) The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the aggregate dryer, at least once daily when the

aggregate dryer is in operation when venting to the atmosphere. Unless operated under conditions for which the Compliance Response Plan specifies otherwise, the pressure drop across the baghouse shall be maintained within the range of 5.0 and 8.0 inches of water or a range established during the latest stack test. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when the pressure reading is outside of the above mentioned range for any one reading. The instrument used for determining the pressure shall comply with Section C - Pressure Gauge Specifications, of this permit, shall be subject to approval by IDEM, OAM, and shall be calibrated at least once every six (6) months.

- (c) An inspection shall be performed each calendar quarter of all bags controlling the aggregate dryer when venting to the atmosphere. A baghouse inspection shall be performed within three months of redirecting vents to the atmosphere and every three months thereafter. Inspections are optional when venting indoors. All defective bags shall be replaced.
- (d) In the event that bag failure has been observed the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Within eight (8) hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) hours of discovery of the failure and shall include a timetable for completion. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions). For single compartment baghouses, failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced.

These monitoring conditions are necessary because the baghouse for the aggregate dryer must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations) 326 IAC 2-2 (Prevention of Significant Deterioration), and 326 IAC 2-8 (FESOP).

Air Toxic Emissions

Indiana presently requests applicants to provide information on emissions of the 188 hazardous air pollutants (HAPs) set out in the 1990 Clean Air Act. These pollutants are either carcinogenic or otherwise considered toxic and are commonly used by industries. They are listed as air toxics on the Office of Air Management (OAM) FESOP Application Form GSD-08.

None of the listed air toxics will be emitted from this source.

- (a) This source will emit levels of air toxics less than those which constitute a major source according to Section 112 of the 1990 Clean Air Act.
- (b) See attached calculations for detailed air toxic calculations. (Appendix A, page 8 of 8)

Conclusion

The operation of this hot batch mix asphalt plant shall be subject to the conditions of the attached proposed **(FESOP No.: F169-12210-00061)**.

Company Name: **Ranger Materials Corporation**
 Plant Location: **Warsaw, IN**
 County: **Wabash**
 Date Recieved: **04/25/2000**
 Permit Reviewer: **PR/EVP**

**** asphalt heating ****

The following calculations determine the amount of emissions created by #2 distillate fuel oil @ 0.49 % sulfur, based on 8760 hours of use and EPA SCC #3-05-002-08:

Pollutant: $\frac{105 \text{ MMBtu/hr} \times 8760 \text{ hr/yr}}{140,000 \text{ Btu/gal} \times 2000 \text{ lb/ton}}$ * Ef (lb/1000 gal) = (ton/yr)

P M:	2.0 lb/1000 gal =	6.57 ton/yr
P M-10:	1.0 lb/1000 gal =	3.29 ton/yr
S O x:	70.0 lb/1000 gal =	229.95 ton/yr
N O x:	20.0 lb/1000 gal =	65.70 ton/yr
V O C:	0.2 lb/1000 gal =	0.66 ton/yr
C O:	5.0 lb/1000 gal =	16.43 ton/yr

**** aggregate drying: drum-mix plant ****

The following calculations determine the amount of emissions created by aggregate drying, based on 8760 hours of use and EPA SCC #3-05-002-05:

P M:	$\frac{32 \text{ lb/ton} \times 160 \text{ ton/hr} \times 8760 \text{ hr/yr}}{2000 \text{ lb/ton}}$	=	22425.6 ton/yr
P M-10:	$\frac{4.5 \text{ lb/ton} \times 160 \text{ ton/hr} \times 8760 \text{ hr/yr}}{2000 \text{ lb/ton}}$	=	3153.6 ton/yr

** conveying / handling **

The following calculations determine the amount of emissions created by material handling of aggregate, based on 8760 hours of use and AP-42, Ch 11.2.3.

$$E_f = .0032 * \frac{(U/5)^{1.3} * k}{(M/2)^{1.4}} = 0.009 \text{ lb/ton}$$

where k = 1 (particle size multiplier)
U = 12 mph mean wind speed (worst case)
M = 2.1 % moisture

$$P M : \frac{0.009 \text{ lb/ton} \times 160 \text{ ton/hr} \times 8760 \text{ hr/yr}}{2000 \text{ lb/ton}} = 6.54 \text{ ton/yr}$$

P M-10: 10% of PM = 0.65 ton/yr

** unpaved roads **

The following calculations determine the amount of emissions created by vehicle traffic on unpaved roads, based on 8760 hours of use and AP-42, Ch 11.2.1.

$$15.2 \text{ trip/hr} \times 0.04 \text{ mile/trip} \times 2 \text{ (round trip)} \times 8760 \text{ hr/yr} = 10652.16 \text{ miles per year}$$

$$E_f = k * 5.9 * (s/12) * (S/30) * (W/3)^{0.7} * (w/4)^{0.5} * ((365-p)/365) = 2.77 \text{ lb/mile}$$

where k = 0.8 size multiplier
s = 5 % silt content of unpaved roads
p = 125 days of rain greater than or equal to 0.01 inches
S = 10 miles/hr vehicle speed
W = 20 tons average vehicle weight
w = 12 wheels

$$\frac{2.77 \text{ lb/mi} \times 10652.16 \text{ mi/yr}}{2000 \text{ lb/ton}} = 14.74 \text{ tons/yr}$$

P M-10: 35% of PM = 5.16 ton/yr

**** storage ****

The following calculations determine the amount of emissions created by wind erosion of storage stockpiles, based on 8760 hours of use and AP-42, Ch 11.2.3.

$$\begin{aligned}
 E_f &= 1.7 \cdot (s/1.5) \cdot (365-p)/235 \cdot (f/15) \\
 &= 5.67 \text{ lb/acre/day} \\
 \text{where } s &= 4.9 \text{ \% silt} \\
 p &= 125 \text{ days of rain greater than or equal to 0.01 inches} \\
 f &= 15 \text{ \% of wind greater than or equal to 12 mph} \\
 E_p (\text{storage}) &= E_f \cdot sc \cdot (20 \text{ cuft/ton}) \cdot (365 \text{ day/yr}) \\
 &\quad (2000 \text{ lb/ton}) \cdot (43560 \text{ sqft/acre}) \cdot (25 \text{ ft}) \\
 &= 0.08 \text{ tons/yr} \\
 \text{where } sc &= 4,000 \text{ tons storage capacity} \\
 P M-10: & \quad 35\% \text{ of PM} = \quad 0.03 \text{ tons/yr}
 \end{aligned}$$

****cold mix VOC storage emissions ****

The following calculations determine the amount of VOC emissions created by the application of cutback asphalt with a typical value of 25% by volume of diluent, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 4.5, Table 4.5-1.

$$\begin{aligned}
 \text{VOC Emission Factor} &= 1.0\% \text{ weight percent flash-off of cold mix} \\
 \text{Potential Throughput (tons/yr)} &= 1,401,600 \text{ tons/yr stockpile mix}
 \end{aligned}$$

$$\begin{aligned}
 \text{Potential VOC Emissions (tons/yr)} &= \text{Potential Throughput (tons/yr)} \cdot \text{wt percent flash-off} \\
 \text{Potential VOC Emissions} &= 13,735.68 \text{ tons/yr}
 \end{aligned}$$

* Weight percent flash-off is based on a 7.0 percent by weight of cutback asphalt, containing 25% by volume of diluent of which 70% volatilizes, in stockpile mix and 24% by weight of cutback asphalt evaporated (from Table 4.5-1).

**** summary of source emissions before controls ****

Criteria Pollutants:	P M:	22453.52 ton/yr	
	P M-10:	3162.72 ton/yr	
	S O x:	229.95 ton/yr	
	N O x:	65.70 ton/yr	
	V O C:	13740.79 ton/yr	(VOCs include HAPs from aggregate drying operation)
	C O:	16.43 ton/yr	

**** source emissions after controls ****

The following calculations determine the amount of emissions created by distillate fuel oil @ 0.49 % sulfur, based on 2,828,571 gallons and EPA SCC #3-05-002-08:

Pollutant:	$\frac{2,828,571 \text{ gal/yr}}{2000 \text{ lb/ton}}$	* Ef (lb/1000 gal) = (ton/yr)
P M:	2.0 lb/1000 gal =	2.83 ton/yr
P M-10:	1.0 lb/1000 gal =	1.41 ton/yr
S O x:	70.0 lb/1000 gal =	99.00 ton/yr
N O x:	20.0 lb/1000 gal =	28.29 ton/yr
V O C:	0.2 lb/1000 gal =	0.28 ton/yr
C O:	5.0 lb/1000 gal =	7.07 ton/yr

** source emissions after controls (continued) **

aggregate drying:				
P M:	22425.6 ton/yr x	0.1%	emitted after controls =	29.15 ton/yr
P M-10:	3153.6 ton/yr x	0.4%	emitted after controls =	12.61 ton/yr
conveying/handling:				
P M:	6.54 ton/yr x	100%	emitted after controls =	6.54 ton/yr
P M-10:	0.65 ton/yr x	100%	emitted after controls =	0.65 ton/yr
unpaved roads:				
P M:	14.74 ton/yr x	100%	emitted after controls =	14.74 ton/yr
P M-10:	5.16 ton/yr x	100%	emitted after controls =	5.16 ton/yr
storage:				
P M:	0.08 ton/yr x	100%	emitted after controls =	0.08 ton/yr
P M-10:	0.03 ton/yr x	100%	emitted after controls =	0.03 ton/yr
cutback VOC storage: fugitive				
VOC:	13,735.68 ton/yr	134.70	Limited Diluent Throughput (tons/yr) =	94.29 ton/yr

Emissions after controls are as follows:

P M:	53.34 ton/yr
P M-10:	19.87 ton/yr
S O x:	99.00 ton/yr
N O x:	28.29 ton/yr
V O C:	99.00 ton/yr
C O:	7.07 ton/yr

* * miscellaneous * *

The following calculations determine the maximum sulfur content of distillate fuel oil allowable by 326-IAC 7:

$$\begin{array}{rcl} 0.5 \text{ lb/MMBtu} \times & 140,000 \text{ Btu/gal} = & 70 \text{ lb/1000gal} \\ 70 \text{ lb/1000gal} / & 144 \text{ lb/1000 gal} = & 0.49 \end{array}$$

Sulfur content must be less than or equal to 0.49% to comply with 326 IAC 7.

PM-10 Emission Limit for Aggregate Dryer:

$$\begin{array}{rcl} (99.0 \text{ tons PM-10/yr} - 7.38 \text{ tons PM-10/yr from other sources}) & & \\ = & 91.62 \text{ tons PM-10/yr} & = 20.92 \text{ lbs/hr} \end{array}$$

PM-10 emissions from the aggregate dryer are controlled to 0.32 lbs/hr < 20.92 lbs/hr (Will comply)

The following calculations determine compliance with 326 IAC 6-3-2 for process weight rates in excess of 30 tons per hour:

$$\begin{array}{rclcl} \text{limit} = & 55 * (& 160 ^{0.11}) - 40 = & 56.12 \text{ lb/hr} & \text{or} & 245.81 \text{ ton/yr} \\ 29.15 \text{ tons/yr} \times & 2000 \text{ lb/ton} / & 8760 \text{ hr/yr} = & 6.66 \text{ lb/hr} & & (\text{will comply}) \end{array}$$

40 CFR Part 60.90, Subpart I (Standards of Performance for Hot Mix Asphalt Plants) Compliance Calculations:

The following calculations determine compliance with the NSPS, which limits stack emissions from asphalt plants to 0.04 gr/dscf:

$$\frac{29.15 \text{ ton/yr} * 2000 \text{ lb/ton} * 7000 \text{ gr/lb}}{525,600 \text{ min/yr} * 27,194 \text{ dscf/min}} = 0.029 \text{ gr/dscf} \quad (\text{will comply})$$

Allowable particulate emissions under NSPS equate to 40.84 tons per year. 9.32 lbs/hr

Note:

$$\begin{array}{rcl} \text{SCFM} = & 39,100 \text{ acfm} * (460 + 68) * (1 - 0.045) / (460 + 265) \\ = & 27,194 \text{ scfm} \end{array}$$

Assumes exhaust gas temperature of 265F, exhaust gas moisture content of 4.5% and exhaust gas flow of 39,100 acfm.

Hazardous Air Pollutants (HAPs)

**** aggregate dryer burner****

The following calculations determine the amount of metallic HAP emissions created by the combustion of distillate fuel oil before & after control: 0.49 % sulfur, from the aggregate dryer burner, based on 8,760 hours of use and US EPA's AP-42, 5th Edition, Section 1.3 - Fuel Oil Combustion, Table 1.3-10.

Hazardous Air Pollutants (HAPs)		105 MMBtu/hr * 8760 hr/yr 2,000 lb/ton	* Ef (lb/10 ¹² Btu) = (ton/yr)	
			Potential To Emit	Limited Emissions
Arsenic:	4	lb/10 ¹² Btu =	1.84E-03 ton/yr	2.39E-06 ton/yr
Beryllium:	3	lb/10 ¹² Btu =	1.38E-03 ton/yr	1.79E-06 ton/yr
Cadmium:	3	lb/10 ¹² Btu =	1.38E-03 ton/yr	1.79E-06 ton/yr
Chromium:	3	lb/10 ¹² Btu =	1.38E-03 ton/yr	1.79E-06 ton/yr
Lead:	9	lb/10 ¹² Btu =	4.14E-03 ton/yr	5.38E-06 ton/yr
Manganese:	6	lb/10 ¹² Btu =	2.76E-03 ton/yr	3.59E-06 ton/yr
Mercury:	3	lb/10 ¹² Btu =	1.38E-03 ton/yr	1.79E-06 ton/yr
Nickel:	3	lb/10 ¹² Btu =	1.38E-03 ton/yr	1.79E-06 ton/yr
Selenium:	15	lb/10 ¹² Btu =	6.90E-03 ton/yr	8.97E-06 ton/yr
		Total HAPs =	1.56E-02 ton/yr	2.03E-05 ton/yr

**** aggregate drying: drum-mix plant ****

The following calculations determine the amount of organic HAP emissions created by aggregate drying before & after controls, based on 8,760 hours of use and USEPA's AP-42, 5th Edition, Section 11.1 - Hot Mix Asphalt Plants, Table 11.1-9 for a drum mix dryer which can be fired with either fuel oil or natural gas. The HAP emission factors represent the worst case emissions (fuel oil combustion).

Pollutant:	Ef	lb/ton x	160	ton/hr x	8760 hr/yr	
			2000	lb/ton		
Hazardous Air Pollutants (HAPs):						
					Potential To Emit	Limited Emissions
Acetaldehyde:		1.30E-03	lb/ton =		0.91 ton/yr	0.91 ton/yr
Acrolein:		2.60E-05	lb/ton =		0.02 ton/yr	0.02 ton/yr
Benzene:		4.10E-04	lb/ton =		0.29 ton/yr	0.29 ton/yr
Ethylbenzene:		3.80E-04	lb/ton =		0.27 ton/yr	0.27 ton/yr
*Formaldehyde:		2.40E-03	lb/ton =		1.68 ton/yr	1.68 ton/yr
Methyl Ethyl Ketone:		2.00E-05	lb/ton =		0.01 ton/yr	0.01 ton/yr
Propionaldehyde:		1.30E-04	lb/ton =		0.09 ton/yr	0.09 ton/yr
Quinone:		1.60E-04	lb/ton =		0.11 ton/yr	0.11 ton/yr
Toluene:		7.50E-04	lb/ton =		0.53 ton/yr	0.53 ton/yr
**Total Polycyclic Organic Matter (POM):		5.810E-04	lb/ton =		0.41 ton/yr	0.41 ton/yr
Xylene:		1.60E-04	lb/ton =		0.11 ton/yr	0.11 ton/yr
Total HAPs =					4.43 ton/yr	4.43 ton/yr

** total POM includes 2-Methylnaphthalene, Acenaphthylene, Anthracene, Fluorene, Naphthalene, Phenanthrene, and Pyrene.

**** summary of source HAP emissions potential to emit ****

Hazardous Air Pollutants (HAPs):

Acetaldehyde:	0.911	ton/yr
Acrolein:	0.018	ton/yr
Arsenic:	0.002	ton/yr
Benzene:	0.287	ton/yr
Beryllium:	0.001	ton/yr
Cadmium:	0.001	ton/yr
Chromium:	0.001	ton/yr
Ethylbenzene:	0.266	ton/yr
Formaldehyde:	1.682	ton/yr
Lead:	0.004	ton/yr
Manganese:	0.003	ton/yr
Mercury:	0.001	ton/yr
Methyl Ethyl Ketone:	0.014	ton/yr
Nickel:	0.001	ton/yr
Propionaldehyde:	0.091	ton/yr
Quinone:	0.112	ton/yr
Selenium:	0.007	ton/yr
Toluene:	0.526	ton/yr
Total POM:	0.407	ton/yr
Xylene:	0.112	ton/yr
Total:	4.449	ton/yr

**** summary of source HAP limited emissions ****

Hazardous Air Pollutants (HAPs):

Acetaldehyde:	0.911	ton/yr
Acrolein:	0.018	ton/yr
Arsenic:	0.000	ton/yr
Benzene:	0.287	ton/yr
Beryllium:	0.000	ton/yr
Cadmium:	0.000	ton/yr
Chromium:	0.000	ton/yr
Ethylbenzene:	0.266	ton/yr
Formaldehyde:	1.682	ton/yr
Lead:	0.000	ton/yr
Manganese:	0.000	ton/yr
Mercury:	0.000	ton/yr
Methyl Ethyl Ketone:	0.014	ton/yr
Nickel:	0.000	ton/yr
Propionaldehyde:	0.091	ton/yr
Quinone:	0.112	ton/yr
Selenium:	0.000	ton/yr
Toluene:	0.526	ton/yr
Total POM:	0.407	ton/yr
Xylene:	0.112	ton/yr
Total:	4.427	ton/yr